



CERTIFICATE NUMBER 18-HG1720154-PDA
EFFECTIVE DATE 26 March 2018
EXPIRATION DATE 25 March 2023
ABS TECHNICAL OFFICE
Hamburg Engineering Department

CERTIFICATE OF Product Design Assessment

This is to certify that a representative of this Bureau did, at the request of

VOSS FLUID GMBH

located at

Luedenscheider Str. 52-54
D-51688 Wipperfuerth
Germany

assess design plans and data for the below listed product. This assessment is a representation by the Bureau as to the degree of compliance the design exhibits with applicable sections of the Rules. This assessment does not waive unit certification or classification procedures required by ABS Rules for products to be installed in ABS classed vessels or facilities. This certificate, by itself, does not reflect that the product is Type Approved. The scope and limitations of this assessment are detailed on the pages attached to this certificate.

Product Tube Coupling

Model VOSSFormSQR

This Product Design Assessment (PDA) Certificate remains valid until expiration date or until the Rules and/or Standards used in the assessment are revised or until there is a design modification warranting design reassessment (whichever occurs first).

Acceptance of product is limited to the "Intended Service" details prescribed in the certificate and as per applicable Rules and Standards.

This Certificate is valid for installation of the listed product on ABS units which exist or are under contract for construction on or previous to the effective date of the ABS Rules and standards applied at the time of PDA issuance. Use of the Product for non-ABS units is subject to agreement between the manufacturer and intended client.

American Bureau of Shipping

Dagmar Gramatzki,
Engineer/Consultant

NOTE: This certificate evidences compliance with one or more of the Rules, Guides, standards or other criteria of ABS or a statutory, industrial or manufacturer's standards. It is issued solely for the use of ABS, its committees, its clients or other authorized entities. Any significant changes to the aforementioned product without approval from ABS will result in this certificate becoming null and void. This certificate is governed by ABS Rules 1-1-A3/5.9 Terms and Conditions of the Request for Product Type Approval and Agreement (2010).

VOSS FLUID GMBH

LUEDENSCHIEDER STR. 52-54

D-51688 WIPPERFUERTH

Germany

Telephone: 49-2267-635657

Fax: 49-2267-639657

Email: fluid@voss.net

Web: www.voss.net

Tier: 3 - Type Approved, unit certification not required

Product: Tube Coupling
Model: VOSSFormSQR
Intended Service:
For use in steel piping systems.

Description:

Couplings' body, nut and clamping ring made of steel/stainless steel, sealing made of FPM or equivalent. Preparation of pipe ends by use of VOSSForm100 pre-assembly machine.

Rating:

Two (2) ranges of couplings (L and S) cover a pressure range up to 800 bar.

Serie L: (light) 6 - 10 mm PN 500 bar, 12 - 18 mm PN 400 bar, 22 - 42 mm 250 bar.

Serie S: (heavy) 6 - 10 mm PN 800 bar, 12 - 16 mm PN 630 bar, 20 - 38 mm 420 bar.

Service Restriction:

- Unit Certification is not required for this product. If the manufacturer or purchaser request an ABS Certificate for compliance with a specification or standard, the specification or standard, including inspection standards and tolerances, must be clearly defined.
- Coupling types with tapered pipe threads are not to be used for toxic and corrosive fluid services and for all services of temperatures exceeding 495°C.
- In Classes I and II piping systems in general, for joining sections of hydraulic pipes and for steering gear-, controllable pitch propeller- and propulsion related hydraulic systems their use is limited to the following restrictions: 6 mm to 20 mm OD for 103 bar; 22 mm to 25 mm OD for 82.8 bar; 28 mm to 42 mm OD for 41.4 bar. In other hydraulic oil systems they may be used without pressure limitation only for connection to equipment, such as pumps, valves, cylinders, accumulators, gauges and hoses.
- Straight-thread O-ring type fittings may be used for connections to equipment in hydraulic oil piping, without pressure and service limitation, but are not to be used for joining sections of pipes.
- For operating temperatures at lower than -18°C all materials used are to be certified for their adequate notch toughness properties.

Comments:

- The manufacturer has provided a declaration about the control of, or the lack of asbestos in this product.
- For pressure ratings higher than the maximum working pressures specified in Section 5.5/Table 1 of DIN EN ISO 8434-1:2007 and for dynamic conditions, the manufacturer shall be consulted as indicated therein.
- The application and installation of the couplings is to be in accordance with manufacturer's specifications and instructions and is to be approved in conjunction with the relevant systems. Special tools and gauges required for installation of these pipe couplings are to be specified and supplied as necessary by the manufacturer. These special tools are to be kept onboard.

Notes/Drawing/Documentation:

Document No. 61070_Fire_ES-4-VOSSForm-BV-10-DKO, Test Report of 21 Sep 2006_WTI - Fire Resistance, Revision: -, Pages: 8.

Document No. AEL 214-06-1_Burst-Vacuum-Extraction_2S plus- ES-4-VOSSForm-BV-10-DK, Test Report of 27 Nov 2006_Voss - Burst Pressure, Revision: -, Pages: 26.

Document No. Assembly instruction VOSSForm, Assembly instruction VOSSForm, Revision: -, Pages: 6.

Document No. C10106_Pulsation-Vibration_ES-4-VOSSForm-BV-10-DKO, Test Report of 7 Dec 2006_IMA - Pulsation Vibration, Revision: -, Pages: 24.

Document No. DS VOSSForm, Data sheet VOSSForm, Revision: -, Pages: 1.

Document No. Product information VOSSForm, Product information VOSSForm, Revision: -, Pages: 4.

Document No. TD SQR-clamping ring, Technical Drawings SQR-clamping ring, Revision: 02, Pages: 8.

Document No. TD SQR-function nut, Technical Drawing SQR-function nut, Revision: 03, Pages: 1.

Document No. VOSS Fluid ISO 14001_2015, ISO 14001_2015 Certificate, Revision: -, Pages: 3.

Document No. VOSS Fluid ISO 50001_2011, ISO 50001_2011 Certificate, Revision: -, Pages: 1.

VOSS FLUID GMBH
LUEDENSCHIEDER STR. 52-54
D-51688 WIPPERFUERTH
Germany
Telephone: 49-2267-635657
Fax: 49-2267-639657
Email: fluid@voss.net
Web: www.voss.net

Tier: 3 - Type Approved, unit certification not required

Document No. VOSS Fluid ISO 9001_2015, ISO 9001_2015 Certificate, Revision: -, Pages: 1.

Terms of Validity:

This Product Design Assessment (PDA) Certificate 18-HG1720154-PDA, dated 26/Mar/2018 remains valid until 25/Mar/2023 or until the Rules or specifications used in the assessment are revised (whichever occurs first).

This PDA is intended for a product to be installed on an ABS classed vessel, MODU or facility which is in existence or under contract for construction on the date of the ABS Rules or specifications used to evaluate the Product.

Use of the Product on an ABS classed vessel, MODU or facility which is contracted after the validity date of the ABS Rules and specifications used to evaluate the Product, will require re-evaluation of the PDA.

Use of the Product for non ABS classed vessels, MODUs or facilities is to be to an agreement between the manufacturer and intended client.

STANDARDS

ABS Rules:

2018 Steel Vessel Rules 1-1-4/7.7, 1-1-Appendix 3 and 4, 4-6-1/7.1.2, 4-6-1/7, 4-6-2/3, 4-6-2/5.5, 4-6-2/5.9, 4-6-2/9.6.

National:

DIN 3861:2016-09, DIN 3870:2001-09.

International:

ISO 8434-1:2007-09.

Government:

NA

EUMED:

NA

OTHERS:

NA